

G500-MB/G600-MB/G700-MB/G800-MB/G1000-MB



700W / 800W / 1000W 165(L)x150(W)x86(H) mm

500W / 600W 160(L)x150(W)x86(H) mm



- Surpassing 80 Plus Gold level with peak 92% efficiency
- 0 Hybrid Modular Cabling Design makes system upgrade and replacement easy
- Anti3s Q-Brick design protects power supply from shock, static electricity, and slip
- Hydraulic Bearing Fan delivers silent, cooling, and durable performance
- Intel Haswell is supported by DC to DC Converter Design to ensure the stability of output voltage when CPU goes into C6/C7 power states
- High efficiency +5Vsb circuit helps system meet EU ErP Lot 6 standard (lower than 1W power consumption at standby mode)
- ATX12V version 2.4 compliant
- Double Forward circuit design provides high efficiency
- Dual Sided PCB design synergizes PCB layout
- Powerful single +12V rail output offers great compatibility with heavy-duty graphics cards
- Over Power, Over Voltage, and Short-circuit protection provide great safety to your system

Specifications

		G500)-MB	G60	0-МВ	G70	0-MB	G80	0-MB	G10	00-MB
AC Input	Input Voltage	100-240VAC, 47-63Hz, Active PFC									
	Input Current	10-5.5A		10-5.5A		15-7.5A		15-7.5A		15-7.5A	
DC Output	+3.3V	21A	103W	21A	103W	24A	130W	24A	130W	24A	- 130W
	+5V	15A		15A		24A		24A		24A	
	+12V	40A	480W	48A	576W	58A	696W	65A	780W	83A	996W
	-12V	0.3A	3.6W	0.3A	3.6W	0.3A	3.6W	0.3A	3.6W	0.3A	3.6W
	+5Vsb	2.5A	12.5W	2.5A	12.5W	2.5A	12.5W	2.5A	12.5W	2.5A	12.5W
	Total Power	500W		600W		700W		800W		1000W	







G500-MB/G600-MB/G700-MB/G800-MB/G1000-MB

Anti3s Q-Brick Design

Anti3s Q-Brick design protects power supply from three aspects 1. Anti-shock 2. Anti-static 3. Anti-slippery



Hybrid Modular Cabling Design

Hybrid modular cabling design makes system upgrade and replacement easy



Connectors

20+4P 4+4P CPU **8P CPU** Main Power • 600W x 1 • 500W x 1 • 800W x 1 • 800W x 1 • 600W x 1 • 1000W x 1 • 1000W x 1 • 1000W x 1 • 700W x 1 • 700W x 1 6+2P(8P) SATA Floppy **4P Molex** PCI-E • 500W x 5 • 500W x 1 • 500W x 2 • 500W x 4 • 600W x 7 • 600W x 1 • 600W x 2 • 600W x 4 • 700W x 1 • 700W x 4 • 700W x 9 • 700W x 4 • 800W x 12 • 800W x 1 • 800W x 4 • 800W x 4 • 1000W x 12 • 1000W x 1 • 1000W x 6 • 1000W x 8 V N4251 Z385



© 2014 LEPA TECHNOLOGY. All right reserved. Specifications are subjects to change without prior notice. All trademarks, registered trademarks and product names mentioned are the property of their respective owners. Oct. 2014

Hydraulic Bearing Fan

Hydraulic Bearing Fan delivers silent, cooling, and durable performance



Intel Haswell Support

Intel Haswell C6/C7 state fully supported by DC to DC circuitry

